

STAINLESS STEEL ROLLING LADDER



450 lb Weight Capacity

The Ballymore Aluminum Ladder delivers lightweight, durable, and safe access with easy mobility — designed for versatile use in a variety of work environments.



FEATURES

- **450 LBS. CAPACITY**
- Ideal for wash down and corrosive environments
- Type T304 Stainless Steel construction
- 1-3 step ladders are all welded and have a 10" deep top step
- 4-12 step ladders have 14" deep top step standard
- Deeper top steps available on all models
- Bead blasted for uniform finish
- Casters for lock step ladders are stainless steel
- Spring Loaded casters are stainless and springs are carbon steel
- Complies with applicable OSHA & ANSI standards
- CAL OSHA available



**SPRING LOADED
CASTER LADDER**



**TILT & ROLL
LADDER**



**FOLD-N-STORE
LADDER**



LOCKSTEP LADDER

SPECIFICATIONS

MODEL #	STEPS INCLUDING TOP STEP	HEIGHT INCHES		BASE W" x L"	WGT Lbs.
		TOP STEP	OVER ALL		
16" WIDE STEP					
SS052414	5 STEP	50"	83"	24 x 46	95
SS062414	6 STEP	60"	93"	24 x 52	105
SS072414	7 STEP	70"	103"	24 x 58	114
SS082414	8 STEP	80"	113"	24 x 64	132
24" WIDE STEP					
SS053214	5 STEP	50"	83"	32 x 46	113
SS063214	6 STEP	60"	93"	32 x 52	126
SS073214	7 STEP	70"	103"	32 x 58	147
SS083214	8 STEP	80"	113"	32 x 64	165
SS093214	9 STEP	90"	123"	32 x 70	180
SS103214	10 STEP	100"	133"	32 x 76	199
SS113214	11 STEP	110"	143"	32 x 82	211
SS123214	12 STEP	120"	153"	32 x 88	227

FOLD-N-STORE			
MODEL #	STEPS INCLUDING TOP STEP	BASE W" x L"	WGT Lbs.
SSFAWL-5	5 STEP	30 x 48	82
SSFAWL-6	6 STEP	30 x 54	92
SSFAWL-7	7 STEP	30 x 60	103
SSFAWL-8	8 STEP	30 x 66	118
SSFAWL-9	9 STEP	30 x 72	133
SSFAWL-10	10 STEP	30 x 78	149
SSFAWL-11	11 STEP	30 x 84	165
SSFAWL-12	12 STEP	30 x 90	180

* Fold-N-Store Capacity = 350 Lbs.

SPRING LOADED CASTERS MODEL #	TILT & ROLL MODEL #	STEPS INCLUDING TOP STEP	HEIGHT INCHES		BASE W" x L"	WGT Lbs.
			TOP STEP	OVERALL		
16" WIDE STEP						
SS1N*	-	1 STEP NO RAILS	12	12	18 x 20	24
SS2N*	-	2 STEP NO RAILS	19	19	20 x 19	28
SS3N*	-	3 STEP NO RAILS	28.5	28.5	20 x 25	35
SS220	SSTR220	2 STEP	19	49	20 x 19	40
SS320	SSTR320	3 STEP	28.5	58.5	20 x 25	46
SS420	SSTR420	4 STEP	40	73	20 x 38	70
SS520	SSTR520	5 STEP	50	83	20 x 44	77
SS624	SSTR624	6 STEP	60	93	24 x 50	81
SS724	-	7 STEP	70	103	24 x 56	95
24" WIDE STEP						
SS2N30*	-	2 STEP NO RAILS	19	19	30 x 19	40
SS3N30*	-	3 STEP NO RAILS	28.5	28.5	30 x 25	44
SS230	SSTR230	2 STEP	19	49	30 x 19	43
SS330	SSTR330	3 STEP	28.5	58.5	30 x 25	55
SS430	SSTR430	4 STEP	40	73	30 x 38	85
SS530	SSTR530	5 STEP	50	83	30 x 44	92
SS630	SSTR630	6 STEP	60	93	30 x 50	105
SS730	-	7 STEP	70	103	30 x 56	115

* Eligible for UPS. Tilt and roll casters add 5" to base length