

SAFETY ANGLE ROLLING LADDER

Features:

- 17" deep top platform
- 50° Safety angle incline
- 450 lb. rated capacity
- Perforated or Grip Strut tread
- Ships unassembled
- 1-1/16" tubular steel rails
- 1" x 2" reinforced back & bottom frame
- 8.5" Deep steps, 10" deep 1st step
- Safety Yellow finish
- Step Lock all models
- Complies with applicable OSHA & ANSI standards



SAFETY ANGLE ROLLING LADDER							
PERFORATED	GRIP STRUT	# of Steps	Step Width	Platform Height	Overall Height	Platform W x L	Base W x D
Tri-Arc Model #	Tri-Arc Model #						
KDEC103166-Y	KDEC103162-Y	3	16"	30"	66"	16" x 17"	27" x 41"
KDEC103246-Y	KDEC103242-Y	3	24"	30"	66"	24" x 17"	35" x 41"
KDEC104166-Y	KDEC104162-Y	4	16"	40"	76"	16" x 17"	27" x 49"
KDEC104246-Y	KDEC104242-Y	4	24"	40"	76"	24" x 17"	35" x 49"
KDEC105166-Y	KDEC105162-Y	5	16"	50"	86"	16" x 17"	27" x 58"
KDEC105246-Y	KDEC105242-Y	5	24"	50"	86"	24" x 17"	35" x 58"
KDEC106166-Y	KDEC106162-Y	6	16"	60"	96"	16" x 17"	27" x 66"
KDEC106246-Y	KDEC106242-Y	6	24"	60"	96"	24" x 17"	35" x 66"
KDEC107166-Y	KDEC107162-Y	7	16"	70"	106"	16" x 17"	27" x 74"
KDEC107246-Y	KDEC107242-Y	7	24"	70"	106"	24" x 17"	35" x 74"
KDEC108246-Y	KDEC108242-Y	8	24"	80"	116"	24" x 17"	35" x 82"
KDEC109246-Y	KDEC109242-Y	9	24"	90"	126"	24" x 17"	35" x 91"
KDEC110246-Y	KDEC110242-Y	10	24"	100"	136"	24" x 17"	35" x 99"
KDEC111246-Y	KDEC111242-Y	11	24"	110"	146"	24" x 17"	35" x 107"
KDEC112246-Y	KDEC112242-Y	12	24"	120"	156"	24" x 17"	35" x 116"
KDEC113246-Y	KDEC113242-Y	13	24"	130"	166"	24" x 17"	40" x 124"
KDEC114246-Y	KDEC114242-Y	14	24"	140"	176"	24" x 17"	40" x 132"
KDEC115246-Y	KDEC115242-Y	15	24"	150"	186"	24" x 17"	40" x 141"
KDEC116246-Y	KDEC116242-Y	16	24"	160"	196"	24" x 17"	43" x 149"